

			AMM190WTD
Display Performance	Inch Size		19inch
	Aspect Ratio		16:10
	LCD Mode		Transmissive, Normally Black Mode. IPS-PRO
	Pixels		H 0.24375mm x V 0.24375mm
	Display Color		16,777,215 Colors
	Luminance		Typ 300cd/m2
	Contrast Ratio		Typ 900:1
	Resolution (H/V)		1680/1050
	Response		21ms (Rise 11ms, Fall 10ms)
	Viewing Angle (H/V)		89/89
	Color Gamut		72%
	Gamma		2.2
General	Power		90V~265V AC/18V 5.6A DC Adaptor
	Dimensions (HxWxD mm)		326.9 X 495.4 X 86
	Weight		6.6Kg
	Mounting		VESA 100mm
Input / Output	Input / Output Connector	SDI	BNC/BNC
		DVI	DVI-I 24pin+5pin female/
		Fiber Optic	None/
		HDMI	None/
		VGA (Analog PC)	D-Sub 15pin female/
		RGB / YPbPr	BNC/BNC
		Y/C	S-Video 4pin/S-Video 4pin
		Composite	BNC/BNC
	Input PC Format		VESA
	Option Slot		None
Remote Control	Serial Remote		RS232
	GPIO		
	Network Remote		
Compliance & Certification	Safety		UL (UL 60601-1) cUL (CAN/CSA-C22.2 No. 601.1-M90) CE (EN 60601-1) AS/NZS 3200-1-0 CCC (GB 4943-2001) CB-ITE (IEC 60950-1) IP:X1
	EMC		FCC (Part 15 Class B) CE (EN 60601-1-2) AS/NZS 3200-1-2 VCCI (Class B) CCC (GB 9254, GB17625.1)
	RoHS		Compliance
Option	DC extension cable (3 types)		5ft, 15ft & 75ft length
	Base Stand		Adjustable high, swivel and tilt base stand